

GE Infrastructure Sensing

The GE Protimeter Mini moisture meters are for general purpose measurement applications in construction materials.

- Pin type
- Moisture scale for simple classification of dry, borderline or damp conditions in materials
- Comfortable to hold and easy to use

General Moisture Measurement Applications

The GE Protimeter Mini moisture meter series has been the choice for thousands of users across the world for

more than 30 years. The enduring popularity and success of these instruments is attributable to their versatility, simple design, robust construction and ease of use.

Typical users include:

- Home inspectors
- Flooring contractors
- Termite pest control officers
- Wood product manufacturers and traders
- Cleaning and floor restoration professionals
- Woodworkers

Mini Protimeter Moisture Meters

Mini is a GE Protimeter product. GE Protimeter has joined other GE high-technology sensing businesses under a new name—GE Infrastructure Sensing.



GE Infrastructure Sensing

Building Surveying

The GE Protimeter Mini is ideal for assessing the moisture condition in buildings. A color-coded scale enables the user to assess the moisture level of wood and dry wall at a glance. The numerical values represent the actual percent moisture content of wood (% MC) and the wood moisture equivalent (WME) of concrete, dry wall and other materials. The Mini can be used to determine if the fabrics of a building are in a dry, borderline or damp condition.

Optional hammer electrode and deep wall probes can be used with the Mini to measure the moisture level at depths in walls and floors, regardless of the surface condition. These options are useful accessories when investigating the cause of moisture problems within buildings.

Quality Control Applications

The GE Protimeter Mini is a precision instrument suitable for a wide range of quality control applications on construction sites, for manufacturers and for storage

environments. Contractors use the meter to assess if plasterwork is sufficiently dry for painting. Manufacturers of wooden products such as furniture, roof trusses and pallets use the Mini for checking the moisture content of timber as delivered, and through the manufacturing process. Home inspectors check moisture levels to assess the risk of mold grade.

When taking readings in awkward positions, the Mini can be used with the moisture probe and lead, supplied as standard with the instrument.



Mini Specifications

Calibration Chart

150 commonly used species

Plug in

Extension pin probe (Included)

Calibration

Check device (Included)

Case

Pouch with belt loop (Included)

Warranty

One year parts and labor

Options

Hammer electrode
Deep wall probes

GE Protimeter Mini

Low cost, analog pin-type moisture meter

Range

6% to 90% numerical label

Display

60 LEDs—green (dry), yellow (at risk) and red (wet)

Part Number

BLD2000

Power

9 V (Included)

GE Protimeter Timbermaster™ Mini

Low cost, digital pin-type moisture meter

Range

7% to 99.9%



Mini kit



Timbermaster Mini kit

Display

Digital, resolution 1/10 of 1%

Species Correction

Nine species groups built in

Part Number

BLD5604

Technical Specifications

Weight, Including Batteries

.330 lbs (150g)

Dimensions

7.02 in x 1.09 in x 1.91 in (180 mm x 28 mm x 49 mm)

Batteries

2 AA (Included)

Measurement Range % WME

6% to 90%

GE Infrastructure Sensing



©2004 GE Infrastructure Sensing, Inc. All rights reserved.
920-086A

All specifications are subject to change for product improvement without notice.
Timbermaster™ is a trademark of GE Infrastructure Sensing, Inc. GE® is a registered trademark of General Electric Co.

T 800 321 4878 • 978 437 1000
F 978 437 1031
E sensing@ge.com
www.gesensing.com/protimeterproducts

GE Infrastructure Sensing
1100 Technology Park Dr.
Billerica, MA 01821